

## Tally 4347-i08 printer specifications



### IBM Compatible Matrix Printer Solutions Built to Last

The Tally 4347-i08 printers represent high throughput print speeds, rugged durability and unsurpassed performance under the most extreme conditions. These workhorse printers guarantee crisp, dark, clear and legible print thanks to the advanced engineering of the 24 pin print head. This head is built for long life and a heavy workload so even in the most challenging operating environment, you can be assured of the best in quality and performance.

Low running costs and durability in the harshest of print environments make these products excellent value for the money.

### Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.



Sample Intelligent Mail Barcode

### HIGHLIGHTS

- Ethernet (10/100BaseT) and Parallel standard.
- Optional; Coax/Twinax; Cx/Tx IPDS, Ethernet IPDS; RS232 Serial
- Prints up to 9 part forms
- Full range of automatic features to minimize user intervention
- Ideal for On-Demand and Batch applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Automatic forms loading and thickness adjustment
- Compatible with a wide range of IBM systems, using interfaces and protocols developed and tested in many installations worldwide

### The Right Connectivity, and Easy to Operate

These products are well matched to IBM systems applications, with a wide range of connectivity compatible with most IBM printers.

Fully automated operation, coupled with the straight through paper path, allows ease of use and virtually eliminates errors caused by user intervention.

#### Models Available:

Tally 4347-i08 - single front tractor printer

Tally 4347-i08-2T - dual tractors - front and rear

## Tally 4347-i08 specifications

<b>Print Speed Throughput</b>	High Speed Draft: 12cpi->840cps 10cpi->700cps 587 pages per hour
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	500 million characters
<b>Memory</b>	128Kb
<b>Standard Connectivity</b>	Ethernet 10/100BaseT, Bi-directional parallel
<b>Optional Connectivity</b>	RS232 Serial, Twinax/Coax, Tx/Cx IPDS, Ethernet IPDS
<b>Emulations</b>	IBM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP <u>Optional IGP Version:</u> IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
<b>Fonts</b>	HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP, Intelligent Mail Bar Code
<b>Consumables</b>	Ribbon: 20 million characters
<b>STD Paper Handling</b>	Push tractor with paper parking and auto gap adjust
<b>Optional Paper Handling</b>	2nd front tractor (user installable), paper pedestal, paper basket, paper cutting device
<b>Paper Type</b>	Continuous forms
<b>Paper Weight</b>	60-120gsm
<b>Paper Size</b>	Length: 3 min, 22 max Width 3 min, 16.5 max
<b>Physical Weight</b>	Approximately 42 lbs
<b>Physical Size</b>	(HxWxD): 11.0 x 24.6 x 17.0 inches
<b>Power Voltage Power</b>	AC 230V and 120V (selectable)
<b>Consumption</b>	60W printing
<b>Workload</b>	48,000 pages per month
<b>Number of Copies</b>	Up to 9 part forms; 2-part forms for rear tractor of 4347-i08-2T +10° to +35°C (+50° to +90°)
<b>Temperature Humidity</b>	20% to 80%
<b>Acoustics</b>	59dB(A)
<b>Warranty</b>	One year on site, next business day

**Note: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.**

GET A QUICK QUOTE. COMPLETE THE FOLLOWING  
AND FAX TO: 817.430.6250

# FAX A QUOTE

**Your Name:**

---

**Phone:**

---

**Your Organization:**

---

**Fax:**

---

**From: TGIMPACTPRINTERS.COM**

---

**Phone: 1.866.430.6202**

---

**Fax: 817.430.6250**

---

**QUOTE REQUEST FOR TALLY 4347-i08**

---

**Additional Information:**

---

---

---