

T2250 SPECIFICATIONS



Tally

The T2150 and T2250 are highly featured, reliable and stylish machines. Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

Highlights at a glance:

- Print speeds up to 900 cps
- 26,000 pages per month workload
- 136 columns
- 24 pin print head produces excellent print quality
- Automatic gap adjustment and quick tear
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.

Sample Intelligent Mail Barcode



Available Configuration:

- **T2250** Standard Product
- **T2250 IGP** with IGP/PJL support

T2250 SPECIFICATIONS

Print Sped	720 cps (Fastest Draft), 600 cps (Draft), 270 cps (DPQ), 180 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	482 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	400 million characters
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Serial RS232
Optional Connectivity	Serial Current Loop (20mA), Ethernet 10/100BaseT
Standard Emulations	IBM ProPrinter XL24, Epson LQ2250, MTPL + Barcode + LCP
Optional Emulations	IGP/PGL, Code V, MT660, Printronix P6000, HP2564C DEC LA 75, ECMA 9011, Eastern Europe, MT50
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and Large Character Printing (LCP)
Consumables	Ribbon: 5 million characters
Standard Paper Handling	Push tractors with paper parking and automatic gap adjustment (AGA).
Optional Paper Handling	Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder.
Number of Copies	Push tractor front: 1 Original + 5 copies; Push tractor rear: 1 Original +1 copy; Single sheet: 1 Original + 5 copies
Paper Type	Continuous forms, single sheets
Paper Weight	60-120 g/m ²
Paper Format	Width: 3" to 16.5"; Length: 3" to 23"
Physical Weight	35 lbs
Physical Size	23.6" x 11.8" x 11.6" (W x D x H)
Noise Level (ISO 7779)	53 dB(A)
Power Voltage	120 V or 230 V (selectable)
Power Consumption	40 Watt printing; <10 W Sleep Mode
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Print Volume	26.000 pages per month
MTBF	10.000 hours
Warranty	1 year return to base
Printer Drivers	Windows 2000/XP/Vista/7; Windows Server 2003/2008

GET A QUICK QUOTE. COMPLETE THE FOLLOWING
AND FAX TO: 817.430.6250

FAX A QUOTE

Your Name:

Phone:

Your Organization:

Fax:

From: TGIMPACTPRINTERS.COM

Phone: 1.866.430.6202

Fax: 817.430.6250

QUOTE REQUEST FOR TALLY T2250

Additional Information:
