

T2265+ SPECIFICATIONS



Tally

The T2265+ and T2280+ are undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in their respective speed segments. They are not just sprinters; reliable, heavy workload output is guaranteed for the many years following their purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.

Sample Intelligent Mail Barcode



Highlights at a glance:

- Print speeds up to 900 cps
- Full range of automatic features minimising operator intervention
- Ideal for ,On-Demand' and ,Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Serial RS232, IBM AS400/iSeries Mainframe Ethernet IPDS

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

The products are well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2265+ and T2280+ printers are the first high speed matrix printers to incorporate Ethernet on-board.

Available Configuration:

- **T2265+** Standard Product

T2265+ SPECIFICATIONS

Print Speed	900 cps (Fastest Draft); 640 cps (Draft), 180 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	610 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million strokes per pin
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/100 BaseT
Optional Connectivity	RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS
Standard Emulations	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP, Genicom ANSI
Optional Emulations	ECAM 9014, MT460D, MT50, IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, tear off and park position
Optional Paper Handling	Additional push tractor (front), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 5 copies
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight	45 lbs
Physical Size	24.5" x 17" x 11" mm (W x D x H)
Acoustic	55 dB(A)
Power Voltage	120 V or 230 V (selectable)
Power Consumption	65 Watt Printing
Temperature	+10° to +35° C; 20% to 80% humidity (not condensing)
Workload	48.000 pages per month
MTBF	10.000 hours
Drivers	Windows 2000/XP/Vista/7 and Server 2003/2008; SAP
Warranty	90 days on-site warranty
Note	For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

GET A QUICK QUOTE. COMPLETE THE FOLLOWING
AND FAX TO: 817.430.6250

FAX A QUOTE

Your Name:

Phone:

Your Organization:

Fax:

From: TGIMPACTPRINTERS.COM

Phone: 1.866.430.6202

Fax: 817.430.6250

QUOTE REQUEST FOR TALLY T2265+

Additional Information:
